

Mediated D. D. 1,5200 400



Macintosh PowerBook 5300c/100

Ordering Information

PowerBook 5300c/100

Order No. M3133LL/A

- PowerBook 5300c/100 computer with 8MB of RAM, built-in 1.4MB Apple SuperDrive, and internal 500MB hard disk drive
- 512K of VRAM; supports 256 colors
- Lithium-ion battery and AC adapter
- PC Card storage tray
- System software version 7.5.2
- PowerBook Mobility Bundle
- Complete setup, learning, and reference documentation
- Limited warranty

PowerBook 5300c/100

Order No. M4488LL/A

- Same as Order No. 3133LL/A but with 16MB of RAM, 750MB hard disk drive, and 1MB of VRAM that supports thousands of colors

Macintosh PowerBook Power Adapter

Order No. M3747LL/A

Macintosh PowerBook Rechargeable Lithium-ion Battery

Order No. M3748LL/A

Macintosh PowerBook 8MB RAM Expansion Card

Order No. M3750LL/A

PowerBook Video Adapter Cable

Order No. M3927LL/A

Apple HDI-30 SCSI Disk Adapter

Order No. M2539LL/A

Apple HDI-30 SCSI System Cable

Order No. M2538LL/A

Apple Color StyleWriter 2200

Order No. M3474LL/A

Product specifications are subject to change. Check with your Apple reseller for the most current information about product specifications and configurations.

Technical Specifications

Microprocessor

- 100-MHz PowerPC 603e

Memory

- 8MB or 16MB of RAM, expandable to 64MB

Storage

- Built-in removable Apple SuperDrive 1.4MB floppy disk drive, which uses high-density floppy disks and reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks
- Internal 500MB or 750MB hard disk drive
- Expansion bay for third-party solutions such as an additional hard disk drive or magneto-optical drive (PC Card storage tray included in box may be inserted into this bay to reduce weight by 0.4 lb.)

Display

- 10.4-in. (diagonal), backlit, active-matrix, color display
- Resolution: 640 by 480 pixels
- Comes in two configurations: one with 512K of VRAM, supporting 256 colors; the other with 1MB of VRAM, supporting thousands of colors
- Black matrix screen reduces glare, clearly defines colors, and improves contrast

Battery

- Lithium-ion battery provides 3 to 5 hours of use before recharge; LED display shows how much battery life remains on each charge
- Battery recharges in 2 hours while computer is shut down or in sleep mode; 4 hours while running
- PowerBook Control Strip lets you monitor time remaining, charge status, and battery usage

PC Card slots (PCMCIA)

- Two PC Card slots that can accommodate two Type I or II PC Cards or one Type III PC Card
- Lets you add industry-standard cards such as Ethernet networking, a wired or wireless modem, storage, or other capabilities

Expansion bay

- IDE connector for third-party solutions such as an additional hard drive, a magneto-optical drive, and other devices
- Power lines for connection of an internal AC adapter and other third-party solutions

Ports

- One Apple Desktop Bus (ADB) port
- One serial (RS-422) port
- One SCSI port for connecting as many as six external devices (including CD-ROM)
- One power adapter port
- Stereo sound input port
- Stereo sound output port
- Video output port

Networking

- Serial/LocalTalk port for AppleTalk connections to networks and printers
- Ethernet networking through PC Cards
- Ultra-easy file sharing through infrared technology—without cable connections or time-consuming setup; supports AppleTalk protocol

Built-in stereo sound

- 16-bit, CD-quality stereo sound capable of driving headphones or external speakers
- Built-in speaker and integrated microphone
- Digital-to-analog conversion sampled at 44.1, 22.05, or 11.025 kHz
- 16 bit, audio line-in for recording

Video output

- 8-bit video output port to support external color displays—compatible with most Apple, VGA, and SVGA monitors (upgradable to greater bit depths through third-party solutions)

Security

- Includes a security slot that secures the system, battery, and expansion bay (requires a third-party accessory)
- Includes password protection software

Keyboard and Apple trackpad

- Built-in, full-size keyboard with 76 (U.S.) or 77 (ISO) keys, including 12 function keys and integrated palm rest
- Power button on keyboard
- Solid-state Apple trackpad provides precise cursor control in response to the movement of the user's fingertip over its surface; sensing of movement and acceleration is easily adjustable through a control panel

Disability access

- System software includes CloseView and Easy Access, and provides the ability to substitute visual cue for beep

Electrical requirements

- Line voltage: 100 to 240 volts AC
- Frequency: 50 to 60 Hz

ADB power requirements

- Maximum current draw for all ADB devices: 200 mA

Environmental requirements

- Operating temperature: 41° to 95° F (5° to 35° C)
- Storage temperature: -13° to 140° F (-25° to 60° C)
- Relative humidity: 20% to 80% noncondensing
- Operating altitude: 0 to 10,000 ft. (0 to 3,048 m)
- Maximum storage altitude: 15,000 ft. (4,722 m)

Size and weight

- Height: 2.2 in. (5.3 cm)
- Width: 11.5 in. (29.2 cm)
- Depth: 8.5 in. (21.6 cm)
- Weight: 6.2 lb. (2.8 kg)

Apple Computer, Inc.
1 Infinite Loop
Cupertino, CA 95014
(408) 996-1010
TLX 171-576

© 1995 Apple Computer, Inc. All rights reserved. Apple, the Apple logo, Apple SuperDrive, AppleTalk, LocalTalk, Macintosh, PowerBook, Power Macintosh, ProDOS, QuickTime, and StyleWriter are trademarks of Apple Computer, Inc., registered in the U.S.A. and other countries. Apple Desktop Bus, eWorld, and Mac are trademarks of Apple Computer, Inc. MS-DOS and Windows are registered trademarks of Microsoft Corporation; SoftWindows is a trademark used under license by Insignia from Microsoft. OS/2 is a registered trademark and PowerPC is a trademark of International Business Machines Corporation, used under license therefrom. Mention of non-Apple products is for informational purposes only and constitutes neither an endorsement nor a recommendation. Apple assumes no responsibility with regard to the selection, performance, or use of these products. All understandings, agreements, or warranties, if any, take place directly between the vendors and the prospective users.
July 1995. Product specifications are subject to change without notice. Printed in U.S.A.
101358A